Heavy Duty ESI
Antifreeze+Coolant

Extended Service Interval Technology

- Formulated for Heavy Duty Vehicles
- Compatible with any IAT coolant
- Nitrited, pre-charged with supplemental coolant additives
- Extended service interval; fully formulated to provide engine protection
- Stabilized, low silicate (no phosphates) formula helps reduce deposits & reduce hard water scale buildup
- Requires monitoring & maintaining additive levels

CONCENTRATE	PACK	UPC
74005	6/3.78 L	6 20235-74005 4
74021	205 L	6 20235-74021 4
74305	1,000 L	6 20235-74305 5
READY TO USE	**PACK**	**UPC**
74013	6/3.78 L	6 20235-74013 9
74039	205 L	6 20235-74039 9
74313	1,000 L	6 20235-74313 0

For Use In: Heavy Duty Vehicles Classes 6-8
Compatibility: ESI & IAT

OEM Approvals/Registrations

Detroit Diesel 93K217

Meets or Exceeds OEM Performance Requirements:

Cummins CES 14439
Cummins CES 90T8-4
Detroit Diesel 7SE298
Mack 014617004
Freightliner 48-25961
Freightliner 48-25878
Navistar CEMS B-1, Type II
Freightliner 48-22880
Kenworth R026-170-97
Peterbilt 8502.002
John Deere H24, H24 A1
John Deere JDS-G135
John Deere 8650-5

Meets or Exceeds Industry & Governmental Standards:

ASTM D6210
ASTM D3306
ASTM D4985
ASTM D4340
TMC RP338A
TMC RP329A
TMC RP351
SAE J1941
SAE J1034
GCA A-A-52624
CID A-A-52624A

PRESTONE COMMAND® is a registered trademark of Prestone Products Corporation.
All other marks are those of their respective owners.

Heavy Duty ESI
Antifreeze+Coolant

74005 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	96.8%
Total Water:	3.2%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Purple/Fuchsia	
Odor:	Characteristic	
Ash Content:	0.50% by weight	Federal #209B
pH at 50 vol%:	10.4	ASTM D1287
Reserve Alkalinity:	5.7 mL	ASTM D1121
Density at 15°C, g/mL:	1.1189	ASTM D1122
Freezing Point at 50 vol%:	-37°C (-34°F)	ASTM D1177
Boiling Point at 50 vol%: *Under standard pressure*	+108°C (+226°F)	ASTM D1120
Foam Test:	50 mL/1.0 sec.	ASTM D1881

74013 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	51%
Total Water:	49%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Purple/Fuchsia	
Odor:	Characteristic	
Ash Content:	0.25% by weight	Federal #209B
pH:	10.4	ASTM D1287
Reserve Alkalinity:	2.8 mL	ASTM D1121
Density at 15°C, g/mL:	1.0696	ASTM D1122
Freezing Point:	-37°C (-34°F)	ASTM D1177
Boiling Point: *Under standard pressure*	+108°C (+226°F)	ASTM D1120
Foam Test:	50 mL/1.0 sec.	ASTM D1881

Most of our COMMAND® Antifreeze+Coolant Products come in 205 L Drums, 1000 L Totes and Bulk.

205 L drum

1,000 L tote

PRESTONE COMMAND® is a registered trademark of Prestone Products Corporation.

©2022 Prestone Products Corporation | www.prestone.com | PA1956